Ruby master - Bug #12392

configure --with-sitedir=no --with-sitearchdir=no --with-vendordir=no --with-vendorarchdir=no

05/18/2016 03:14 PM - yoko-a (Atsushi YOKOYAMA)

Status:	Open		
Priority:	Normal		
Assignee:			
Target version:			
ruby -v:	ruby 2.3.1p112 (2016-04-26 revision 54768) [x86_64-linux]	**Backport:**	2.1: UNKNOWN, 2.2: UNKNOWN, 2.3: UNKNOWN

Description

configure --with-sitedir, --with-sitearchdir, --with-vendordir, --with-vendorarchdir no

make install

```
% ./configure --with-sitedir=no --with-sitearchdir=no --with-vendordir=no --with-vendorarchdir=no
% make
% sudo make install
% ls -l | head -3
total 147396
drwxr-xr-x  3 root   root       4096 May 18 23:51 $(sitedir)/
drwxr-xr-x  3 root   root       4096 May 18 23:51 $(vendordir)/
%

% ruby -e 'puts $:.join("\n")'
/usr/local/lib/ruby/gems/2.3.0/gems/did_you_mean-1.0.0/lib
${sitedir}/2.3.0
${sitearchdir}
${sitedir}
${vendordir}/2.3.0
${vendorarchdir}
${vendordir}
/usr/local/lib/ruby/2.3.0
/usr/local/lib/ruby/2.3.0/x86_64-linux
%
```