

Ruby master - Misc #12439

[PATCH cleanup] process.c (disable_child_handler_fork_child): simplify

05/31/2016 12:58 AM - normalperson (Eric Wong)

Status:	Closed	
Priority:	Normal	
Assignee:	akr (Akira Tanaka)	
Description		
process.c (disable_child_handler_fork_child): simplify		
signal(2) is portable for SIG_DFL and SIG_IGN, so we do not need the extra code for sigaction(2).		
Also, execve will reset all signal handlers to default anyways, so there is little sense in preserving old signal handler besides SIG_IGN.		
Hopefully this makes the code easier-to-understand and maintain.		
Comments? Will commit in a week or two if no response. Thanks.		

Associated revisions

Revision 80a0c0f8 - 07/02/2016 09:13 PM - normal

process.c (disable_child_handler_fork_child): simplify

signal(2) is portable for SIG_DFL and SIG_IGN, so we do not need the extra code for sigaction(2).

Also, execve will reset all signal handlers to default anyways, so there is little sense in preserving old signal handler besides SIG_IGN.

Hopefully this makes the code easier-to-understand and maintain.

- process.c (disable_child_handler_fork_child): simplify [ruby-core:75781] [Misc #12439]

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@55566 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision 55566 - 07/02/2016 09:13 PM - normalperson (Eric Wong)

process.c (disable_child_handler_fork_child): simplify

signal(2) is portable for SIG_DFL and SIG_IGN, so we do not need the extra code for sigaction(2).

Also, execve will reset all signal handlers to default anyways, so there is little sense in preserving old signal handler besides SIG_IGN.

Hopefully this makes the code easier-to-understand and maintain.

- process.c (disable_child_handler_fork_child): simplify [ruby-core:75781] [Misc #12439]

Revision 55566 - 07/02/2016 09:13 PM - normal

process.c (disable_child_handler_fork_child): simplify

signal(2) is portable for SIG_DFL and SIG_IGN, so we do not need the extra code for sigaction(2).

Also, execve will reset all signal handlers to default anyways, so there is little sense in preserving old

signal handler besides SIG_IGN.

Hopefully this makes the code easier-to-understand and maintain.

- process.c (disable_child_handler_fork_child): simplify [ruby-core:75781] [Misc #12439]

Revision 55566 - 07/02/2016 09:13 PM - normal

process.c (disable_child_handler_fork_child): simplify

signal(2) is portable for SIG_DFL and SIG_IGN, so we do not need the extra code for sigaction(2).

Also, execve will reset all signal handlers to default anyways, so there is little sense in preserving old signal handler besides SIG_IGN.

Hopefully this makes the code easier-to-understand and maintain.

- process.c (disable_child_handler_fork_child): simplify [ruby-core:75781] [Misc #12439]

Revision 55566 - 07/02/2016 09:13 PM - normal

process.c (disable_child_handler_fork_child): simplify

signal(2) is portable for SIG_DFL and SIG_IGN, so we do not need the extra code for sigaction(2).

Also, execve will reset all signal handlers to default anyways, so there is little sense in preserving old signal handler besides SIG_IGN.

Hopefully this makes the code easier-to-understand and maintain.

- process.c (disable_child_handler_fork_child): simplify [ruby-core:75781] [Misc #12439]

History

#1 - 04/28/2017 01:45 PM - shyouhei (Shyouhei Urabe)

- Status changed from Open to Assigned

#2 - 10/21/2017 07:13 AM - akr (Akira Tanaka)

- Status changed from Assigned to Closed

It seems already committed.

Files

0001-process.c-disable_child_handler_fork_child-simplify.patch	3.13 KB	05/31/2016	normalperson (Eric Wong)
----------------------------------------------------------------	---------	------------	--------------------------