

Ruby trunk - Bug #12563

backport 49758,50356

07/06/2016 08:40 PM - naruse (Yui NARUSE)

Status: Closed	
Priority: Normal	
Assignee:	
Target version:	
ruby -v: ruby 2.2.6p342 (2016-07-07 revision 55599) [x86_64-freebsd10.3]	Backport: 2.1: UNKNOWN, 2.2: DONE, 2.3: DONTNEED
Description 49758,50356 is required to run make test-rubyspec because without them rubyspec fails to build option/capi/ext. https://travis-ci.org/ruby/ruby/builds/142788121	

Associated revisions

Revision f54265a8 - 07/11/2016 03:17 PM - usa (Usaku NAKAMURA)

merge revision(s) 49758,50356,50359: [Backport #12563]

```
fake.rb: rubyarchhdrdir for rubyspec
```

```
* common.mk (test-rubyspec): use fake script to set header
```

directories.

```
* template/fake.rb.in (RUBYOPT): set -r option to propagate to
```

forked processes.

```
* tool/fake.rb (prehook): set rubyarchhdrdir too.
```

```
* too/fake.rb: don't fake libdir. use libdirname instead.
```

```
* tool/fake.rb: don't fake libdir. use libdirname instead.
```

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/branches/ruby_2_2@55637 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision 55637 - 07/11/2016 03:17 PM - usa (Usaku NAKAMURA)

merge revision(s) 49758,50356,50359: [Backport #12563]

```
fake.rb: rubyarchhdrdir for rubyspec
```

```
* common.mk (test-rubyspec): use fake script to set header
```

directories.

```
* template/fake.rb.in (RUBYOPT): set -r option to propagate to
```

forked processes.

```
* tool/fake.rb (prehook): set rubyarchhdrdir too.
```

```
* too/fake.rb: don't fake libdir. use libdirname instead.
```

```
* tool/fake.rb: don't fake libdir. use libdirname instead.
```

History

#1 - 07/11/2016 03:18 PM - usa (Usaku NAKAMURA)

- Backport changed from 2.1: UNKNOWN, 2.2: REQUIRED, 2.3: DONTNEED to 2.1: UNKNOWN, 2.2: DONE, 2.3: DONTNEED

ruby_2_2 r55637 merged revision(s) 49758,50356,50359.