

## Ruby trunk - Bug #13336

### Default Parameters don't work

03/20/2017 05:34 PM - herbert.bonaffini@gmail.com (Herbert Bonaffini)

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Target version:</b>	
<b>ruby -v:</b> 2.3.1	<b>Backport:</b> 2.2: UNKNOWN, 2.3: UNKNOWN, 2.4: UNKNOWN
<b>Description</b> <pre>def funny(a = true, b: nil)   p a end  funny([1,2,3]) # =&gt; [1,2,3]  funny({k:1}) # =&gt; in `funny': unknown keyword: k (ArgumentError)</pre>	
<b>Related issues:</b>	
Related to Ruby trunk - Feature #14183: "Real" keyword argument	<b>Open</b>
Is duplicate of Ruby trunk - Bug #12717: Optional argument treated as kwarg	<b>Open</b>

### History

#### #1 - 05/19/2017 06:43 AM - ko1 (Koichi Sasada)

- Description updated

#### #2 - 05/19/2017 06:47 AM - ko1 (Koichi Sasada)

- Assignee set to mame (Yusuke Endoh)

mame-san: what do you think about it?

#### #3 - 05/19/2017 06:48 AM - nobu (Nobuyoshi Nakada)

- Assignee deleted (mame (Yusuke Endoh))

- Description updated

#### #4 - 05/19/2017 04:16 PM - mame (Yusuke Endoh)

This is intended. If a method accepts keyword arguments and if its last argument is a hash object, it is considered for keyword arguments. If you want to pass a hash as the first parameter, you need to explicitly pass a hash for keyword arguments, i.e., `funny({k: 1}, {})`.

#### #5 - 12/14/2017 07:25 AM - hsbt (Hiroshi SHIBATA)

- Related to Feature #14183: "Real" keyword argument added

#### #6 - 09/05/2018 03:25 PM - marcandre (Marc-Andre Lafortune)

- Status changed from Open to Closed

This is a duplicate of [#12717](#), so closing this.

#### #7 - 09/05/2018 03:26 PM - marcandre (Marc-Andre Lafortune)

- Is duplicate of Bug #12717: Optional argument treated as kwarg added

### Files

hello_bug.rb	132 Bytes	03/20/2017	herbert.bonaffini@gmail.com (Herbert Bonaffini)
--------------	-----------	------------	---