

Ruby trunk - Bug #14345

http_proxy setting should respect both parent domain and subdomain

01/10/2018 12:12 AM - harsimranmaan (Harsimran Singh Maan)

Status: Closed	
Priority: Normal	
Assignee:	
Target version:	
ruby -v: master	Backport: 2.3: UNKNOWN, 2.4: UNKNOWN, 2.5: UNKNOWN

Description

When a ruby app is run in an environment where an http proxy is configured, it is not possible to provide separate settings for both a domain and it's subdomain for outbound http calls. This coupling assumes that both should follow the same http_proxy settings but in practice, this is a common occurrence the parent domain and the subdomains are be hosted on different network.

<https://github.com/ruby/ruby/pull/1748> addresses this issues.

Also note that other programming language like go respect different proxy settings for parent domain and its subdomains.

https://github.com/golang/go/blob/master/src/net/http/proxy_test.go#L37

Associated revisions

Revision d50ecb63 - 05/17/2018 07:40 AM - naruse (Yui NARUSE)

http_proxy setting should respect both parent domain and subdomain

URI::Generic: Respect no_proxy for both parent domain and subdomains It is now possible to add just the subdomains for proxy bypass. In a setting where the main domain needs to go through proxy while the subdomains don't, it is now possible to just add the subdomains to the no_proxy list.

The assumption that subdomains and the parent domain should behave the same wrt no_proxy has been removed.

eg: Adding .example.com in no_proxy would allow example.com to go through the proxy.

From: Harsimran Singh Maan maan.harry@gmail.com
fix <https://github.com/ruby/ruby/pull/1748>
[Bug #14345]

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@63452 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision 63452 - 05/17/2018 07:40 AM - naruse (Yui NARUSE)

http_proxy setting should respect both parent domain and subdomain

URI::Generic: Respect no_proxy for both parent domain and subdomains It is now possible to add just the subdomains for proxy bypass. In a setting where the main domain needs to go through proxy while the subdomains don't, it is now possible to just add the subdomains to the no_proxy list.

The assumption that subdomains and the parent domain should behave the same wrt no_proxy has been removed.

eg: Adding .example.com in no_proxy would allow example.com to go through the proxy.

From: Harsimran Singh Maan maan.harry@gmail.com
fix <https://github.com/ruby/ruby/pull/1748>
[Bug #14345]

Revision 63452 - 05/17/2018 07:40 AM - naruse (Yui NARUSE)

http_proxy setting should respect both parent domain and subdomain

URI::Generic: Respect no_proxy for both parent domain and subdomains It is now possible to add just the subdomains for proxy bypass. In

a setting where the main domain needs to go through proxy while the subdomains don't, it is now possible to just add the subdomains to the no_proxy list.

The assumption that subdomains and the parent domain should behave the same wrt no_proxy has been removed.

eg: Adding .example.com in no_proxy would allow example.com to go through the proxy.

From: Harsimran Singh Maan maan.harry@gmail.com

fix <https://github.com/ruby/ruby/pull/1748>

[Bug #14345]

History

#1 - 02/01/2018 02:47 AM - harsimranmaan (Harsimran Singh Maan)

Any updates here?

#2 - 03/24/2018 01:58 PM - shevegen (Robert A. Heiler)

I think this will be discussed at the next ruby developer meeting in April 2018 so stay tuned for updates to it (less than a month to go for the next developer meeting).

See here:

<https://bugs.ruby-lang.org/projects/ruby/wiki/DevelopersMeeting20180419Japan>

#3 - 05/17/2018 07:40 AM - naruse (Yui NARUSE)

- Status changed from Open to Closed

Applied in changeset [trunk|r63452](#).

http_proxy setting should respect both parent domain and subdomain

URI::Generic: Respect no_proxy for both parent domain and subdomains It is now possible to add just the subdomains for proxy bypass. In a setting where the main domain needs to go through proxy while the subdomains don't, it is now possible to just add the subdomains to the no_proxy list.

The assumption that subdomains and the parent domain should behave the same wrt no_proxy has been removed.

eg: Adding .example.com in no_proxy would allow example.com to go through the proxy.

From: Harsimran Singh Maan maan.harry@gmail.com

fix <https://github.com/ruby/ruby/pull/1748>

[Bug #14345]