

## Ruby master - Bug #2469

### Difference behavior of IO#read\_nonblock and #read between 1.8 and 1.9

12/10/2009 07:18 AM - ujihisa (Tatsuhiko Ujihisa)

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b> ko1 (Koichi Sasada)	
<b>Target version:</b> 2.0.0	
<b>ruby -v:</b> ruby 1.9.2dev (2009-12-10 trunk 26055) [i386-darwin9.8.0]	<b>Backport:</b>

#### Description

=begin

The following code doesn't finish on ruby 1.9 (both 1.9.1 and 1.9.2dev), while finishes with Errno::EAGAIN on ruby 1.8.7.

```
read, write = IO.pipe
write << 'hello'
read.read_nonblock(5)
read.read(5)
```

I checked it on i386-darwin9.8.0 and i686-linux.

(This code is extracted from spec/rubyspec/core/io/read\_nonblock\_spec.rb)

=end

#### History

#1 - 12/10/2009 09:13 AM - ujihisa (Tatsuhiko Ujihisa)

- Status changed from Assigned to Closed

- % Done changed from 0 to 100

=begin

[ruby-dev:25101] <http://blade.nagaokaut.ac.jp/cgi-bin/scat.rb/ruby/ruby-dev/25101>

=end