

Ruby master - Feature #2470

Encoding#new doesn't undef_method-ed

12/10/2009 08:03 AM - naruse (Yui NARUSE)

Status:	Closed
Priority:	Normal
Assignee:	
Target version:	
Description	
<pre>=begin Fixnum rb Encoding rb_undef_alloc_func rb_undef_alloc_func Hoge.new rb_undef_alloc_func Fixnum rb_undef_alloc_func Fixnum.new rb_undef_alloc_func Encoding rb_undef_alloc_func rb_undef_alloc_func rb_undef_alloc_func irb(main):001:0> Fixnum.new NoMethodError: undefined method new' for Fixnum:Class from (irb):1 from /usr/local/bin/irb_1_9_1:12:in' irb(main):002:0> Encoding.new TypeError: allocator undefined for Encoding from (irb):2:in new' from (irb):2 from /usr/local/bin/irb_1_9_1:12:in' rb_undef_alloc_func diff --git a/encoding.c b/encoding.c index 38d81b8..f9d2f20 100644 --- a/encoding.c +++ b/encoding.c @@ -1484,6 +1484,7 @@ Init_Encoding(void) rb_cEncoding = rb_define_class("Encoding", rb_cObject); rb_undef_alloc_func(rb_cEncoding); rb_undef_method(CLASS_OF(rb_cEncoding), "new"); rb_define_method(rb_cEncoding, "to_s", enc_name, 0); rb_define_method(rb_cEncoding, "inspect", enc_inspect, 0); rb_define_method(rb_cEncoding, "name", enc_name, 0); diff --git a/object.c b/object.c index 10eb983..704cb2a 100644 --- a/object.c +++ b/object.c @@ -2680,6 +2680,7 @@ Init_Object(void) rb_cData = rb_define_class("Data", rb_cObject); rb_undef_alloc_func(rb_cData); rb_undef_method(CLASS_OF(rb_cData), "new"); rb_cTrueClass = rb_define_class("TrueClass", rb_cObject); rb_define_method(rb_cTrueClass, "to_s", true_to_s, 0); diff --git a/vm.c b/vm.c index fa028fd..e522c9f 100644 --- a/vm.c +++ b/vm.c @@ -1944,6 +1944,7 @@ Init_VM(void) /* ::VM */ rb_cRubyVM = rb_define_class("RubyVM", rb_cObject); rb_undef_alloc_func(rb_cRubyVM); rb_undef_method(CLASS_OF(rb_cRubyVM), "new");</pre>	

```
/* ::VM::FrozenCore /
fcore = rb_class_new(rb_cBasicObject);
@@ -1962,6 +1963,7 @@ Init_VM(void)
/::VM::Env */
rb_cEnv = rb_define_class_under(rb_cRubyVM, "Env", rb_cObject);
rb_undef_alloc_func(rb_cEnv);

• rb_undef_method(CLASS_OF(rb_cEnv), "new");

/* ::Thread */
rb_cThread = rb_define_class("Thread", rb_cObject);
=end
```

History

#1 - 12/10/2009 09:05 AM - naruse (Yui NARUSE)

```
=begin
Data.new
=end
```

#2 - 12/21/2009 07:17 PM - naruse (Yui NARUSE)

- Status changed from Open to Closed
- % Done changed from 0 to 100

```
=begin
This issue was solved with changeset r26145.
Yui, thank you for reporting this issue.
Your contribution to Ruby is greatly appreciated.
May Ruby be with you.
=end
```