

Ruby trunk - Feature #2746

configure --with-exts

02/15/2010 01:36 PM - mrkn (Kenta Murata)

Status:	Closed
Priority:	Normal
Assignee:	
Target version:	2.0.0

Description

=begin

```
make EXTS
make
dbm, gdbm, sdbm, tk
```

```
configure.in --with-exts
--with-exts
```

(1) --with-exts

(2) =
: bigdecimal, fiber, openssl, socket, zlib
--with-exts=bigdecimal,fiber,openssl,socket,zlib

(3) -=
: dbm, gdbm, sdbm, tk,win32ole
--with-exts=-dbm,gdbm,sdbm,tk,win32ole

(4) --without-exts

```
make EXTS
(1-3)
```

```
diff --git a/Makefile.in b/Makefile.in
index a4848d8..b5afa68 100644
--- a/Makefile.in
+++ b/Makefile.in
@@ -96,6 +96,8 @@ THREAD_MODEL = @THREAD_MODEL@
PREP      = @PREP@
ARCHFILE  = @ARCHFILE@
SETUP     =
+EXTS     = @EXTS@
+EXTMK_EXTENSION = @EXTMK_EXTENSION@
EXTSTATIC = @EXTSTATIC@
SET_LC_MESSAGES = env LC_MESSAGES=C
```

```
diff --git a/common.mk b/common.mk
index 74f9f7..b74eb65 100644
--- a/common.mk
+++ b/common.mk
@@ -103,7 +103,7 @@ SCRIPT_ARGS = --dest-dir="$(DESTDIR)" \
--extout="$(EXTOUT)" \
--mflags="$(MFLAGS)" \
--make-flags="$(MAKEFLAGS)"
-EXTMK_ARGS = $(SCRIPT_ARGS) --extension $(EXTS) --extstatic $(EXTSTATIC) \
+EXTMK_ARGS = $(SCRIPT_ARGS) $(EXTMK_EXTENSION) --extstatic $(EXTSTATIC) \
--make-flags="MINIRUBY='$(MINIRUBY)'" --
INSTRUBY = $(MINIRUBY) $(srcdir)/tool/rbinstall.rb
INSTRUBY_ARGS = $(SCRIPT_ARGS) \
diff --git a/configure.in b/configure.in
index d65f481..e3c7f23 100644
```

```

--- a/configure.in
+++ b/configure.in
@@ -1918,6 +1918,40 @@ AS_CASE(["$target_os"],
[nextstep* | openstep* | rhapsody* | darwin*], [
STRIP='strip -A -n']

+EXTS=
+AC_SUBST(EXTS)dnl
+EXTMK_EXTENSION="--extension \$(EXTS)"
+AC_SUBST(EXTMK_EXTENSION)
+AC_ARG_WITH(exts,
    • AS_HELP_STRING([--with-exts=EXTS],
    • [build with external modules;
    • if you specify the name list leading minus sign,
    • the modules is not builded]),
    • [exts="$withval"], [unset exts]) +AC_MSG_CHECKING([builded extensions]) +if test x"$exts" = x -o x"$exts" = xno; then
    • EXTMK_EXTENSION=no-extension
    • AC_MSG_RESULT([no]) +elif test x"$exts" = xyes; then
    • AC_MSG_RESULT([all]) +else
    • if echo "$exts" | grep -q ` 2>/dev/null; then
    • for name in `ls -1 ${srcdir}/ext; do
    • if test -f ${srcdir}/ext/${name}/extconf.rb; then
    • echo $exts | grep -q $name 2>/dev/null || \
    • EXTS=${EXTS},${name}
    • fi
    • done
    • else
    • exts=echo $exts | tr , ' '
    • for name in $exts; do
    • test -f ${srcdir}/ext/${name}/extconf.rb && EXTS=${EXTS},${name}
    • done
    • fi
    • EXTS=echo $EXTS | sed -e 's/^\s/'
    • AC_MSG_RESULT([$EXTS]) +fi + EXTSTATIC= AC_SUBST(EXTSTATIC)dnl AC_ARG_WITH(static-linked-ext, =end

```

History

#1 - 02/15/2010 01:49 PM - matz (Yukihiko Matsumoto)

```
=begin
@@@
```

In message "Re: [ruby-dev:40418] [Feature #2746] @@@@ configure @@@@ --with-exts @@@@"
on Mon, 15 Feb 2010 13:36:10 +0900, Kenta Murata redmine@ruby-lang.org writes:

```

| make @@@@ EXTS @@@@
| make @@@@
| dbm, gdbm, sdbm, tk @@@@
| @@@@
| @@@@configure.in @ --with-exts @@@@

```

```

@@@
@@@

```

```
=end
```

#2 - 02/15/2010 01:59 PM - mrkn (Kenta Murata)

```
=begin
@@@
```

On 2010/02/15, at 13:49, Yukihiko Matsumoto wrote:

```
@@@
```

In message "Re: [ruby-dev:40418] [Feature #2746] @@@@ configure @@@@ --with-exts @@@@"
on Mon, 15 Feb 2010 13:36:10 +0900, Kenta Murata redmine@ruby-lang.org writes:

```
| make @@@@ EXTS @@@@
```

```
| make EXTS
| dbm, gdbm, sdbm, tk
|
| configure.in --with-exts
|
|
```

--
Kenta Murata
OpenPGP FP = FA26 35D7 4F98 3498 0810 E0D5 F213 966F E9EB 0BCC

!!
Ruby <http://www.amazon.co.jp/dp/4798119881/mrkn-22>

E-mail: mrkn@mrkn.jp
twitter: <http://twitter.com/mrkn/>
blog: <http://d.hatena.ne.jp/mrkn/>

=end

#3 - 02/15/2010 02:10 PM - mrkn (Kenta Murata)

=begin

On 2010/02/15, at 13:59, Kenta Murata wrote:

On 2010/02/15, at 13:49, Yukihiro Matsumoto wrote:

In message "Re: [ruby-dev:40418] [Feature #2746] configure --with-exts" on Mon, 15 Feb 2010 13:36:10 +0900, Kenta Murata redmine@ruby-lang.org writes:

```
| make EXTS
| make
| dbm, gdbm, sdbm, tk
|
| configure.in --with-exts
|
|
```

bigdecimal

--
Kenta Murata
OpenPGP FP = FA26 35D7 4F98 3498 0810 E0D5 F213 966F E9EB 0BCC

!!
Ruby <http://www.amazon.co.jp/dp/4798119881/mrkn-22>

E-mail: mrkn@mrkn.jp
twitter: <http://twitter.com/mrkn/>
blog: <http://d.hatena.ne.jp/mrkn/>

=end

#4 - 02/15/2010 02:29 PM - matz (Yukihiro Matsumoto)

ext/extmk.rb

U.Nakamura

usa@garbagecollect.jp

=end

#7 - 02/16/2010 12:06 PM - mrkn (Kenta Murata)

=begin

On 2010/02/15, at 21:37, U.Nakamura wrote:

configure --with-exts

In message "[ruby-dev:40418] [Feature #2746] configure --with-exts" on Feb.15,2010 13:36:10, redmine@ruby-lang.org wrote:

```
make EXTS
make
dbm, gdbm, sdbm, tk
```

configure.in --with-exts

--with-ext(--with-extensions)
ext/extmk.rb

extmk.rb --with-ext --without-ext EXTS
configure.in AC_SUBST(EXTS) --with-exts
extmk.rb

configure EXTS=--without-ext=*dbm,tk,win32api

diff --git a/Makefile.in b/Makefile.in
index a4848d8..14071f8 100644
--- a/Makefile.in
+++ b/Makefile.in
@@ -96,6 +96,7 @@ THREAD_MODEL = @THREAD_MODEL@
PREP = @PREP@
ARCHFILE = @ARCHFILE@
SETUP =
+EXTS = @EXTS@
EXTSTATIC = @EXTSTATIC@
SET_LC_MESSAGES = env LC_MESSAGES=C

diff --git a/configure.in b/configure.in
index d65f481..667c9b4 100644
--- a/configure.in
+++ b/configure.in
@@ -1918,6 +1918,7 @@ AS_CASE(["\$target_os"],
[nextstep* | openstep* | rhapsody* | darwin*], [
STRIP='strip -A -n'])

+AC_SUBST(EXTS)dnl
EXTSTATIC=
AC_SUBST(EXTSTATIC)dnl
AC_ARG_WITH(static-linked-ext,

Kenta Murata
OpenPGP FP = FA26 35D7 4F98 3498 0810 E0D5 F213 966F E9EB 0BCC

Ruby http://www.amazon.co.jp/dp/4798119881/mrkn-22

E-mail: mrkn@mrkn.jp
twitter: http://twitter.com/mrkn/

--

Kenta Murata

OpenPGP FP = FA26 35D7 4F98 3498 0810 E0D5 F213 966F E9EB 0BCC

Ruby !!

Ruby <http://www.amazon.co.jp/dp/4798119881/mrkn-22>

E-mail: mrkn@mrkn.jp

twitter: <http://twitter.com/mrkn/>

blog: <http://d.hatena.ne.jp/mrkn/>

=end

#10 - 03/25/2010 12:15 PM - mrkn (Kenta Murata)

- Status changed from Open to Closed

=begin

=end