

- vm_core.h: Introduce UNINITIALIZED_VAR() macro. * thread.c (do_select): Use UNINITIALIZED_VAR() instead FAKE_FD_ZERO(). Also, remove FAKE_FD_ZERO completely. [Feature #3018]

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@27238 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision 27238 - 04/06/2010 02:07 PM - kosaki (Motohiro KOSAKI)

- vm_core.h: Introduce UNINITIALIZED_VAR() macro.
 - thread.c (do_select): Use UNINITIALIZED_VAR() instead FAKE_FD_ZERO(). Also, remove FAKE_FD_ZERO completely. [Feature #3018]

Revision 27238 - 04/06/2010 02:07 PM - kosaki (Motohiro KOSAKI)

- vm_core.h: Introduce UNINITIALIZED_VAR() macro.
 - thread.c (do_select): Use UNINITIALIZED_VAR() instead FAKE_FD_ZERO(). Also, remove FAKE_FD_ZERO completely. [Feature #3018]

Revision 27238 - 04/06/2010 02:07 PM - kosaki (Motohiro KOSAKI)

- vm_core.h: Introduce UNINITIALIZED_VAR() macro.
 - thread.c (do_select): Use UNINITIALIZED_VAR() instead FAKE_FD_ZERO(). Also, remove FAKE_FD_ZERO completely. [Feature #3018]

Revision 27238 - 04/06/2010 02:07 PM - kosaki (Motohiro KOSAKI)

- vm_core.h: Introduce UNINITIALIZED_VAR() macro.
 - thread.c (do_select): Use UNINITIALIZED_VAR() instead FAKE_FD_ZERO(). Also, remove FAKE_FD_ZERO completely. [Feature #3018]

Revision 27238 - 04/06/2010 02:07 PM - kosaki (Motohiro KOSAKI)

- vm_core.h: Introduce UNINITIALIZED_VAR() macro.
 - thread.c (do_select): Use UNINITIALIZED_VAR() instead FAKE_FD_ZERO(). Also, remove FAKE_FD_ZERO completely. [Feature #3018]

Revision 27238 - 04/06/2010 02:07 PM - kosaki (Motohiro KOSAKI)

- vm_core.h: Introduce UNINITIALIZED_VAR() macro.
 - thread.c (do_select): Use UNINITIALIZED_VAR() instead FAKE_FD_ZERO(). Also, remove FAKE_FD_ZERO completely. [Feature #3018]

History

#1 - 03/27/2010 09:17 AM - ko1 (Koichi Sasada)

```
=begin
#####
```

(2010/03/26 22:40), Motohiro KOSAKI wrote::

```
Linux#####
#####
```

```
#define uninitialized_var(x) x = x
```

```
#####
#####Linux#####
#####
```

```
# #####
```

```
--
// SASADA Koichi at atdot dot net
```

```
=end
```

#2 - 03/27/2010 01:58 PM - kosaki (Motohiro KOSAKI)

```
=begin
2010032709:17 SASADA Koichi ko1@atdot.net:
```

```
#####
```

(2010/03/26 22:40), Motohiro KOSAKI wrote::

```
Linux

```

```
#define uninitialized_var(x) x = x

```

```

Linux

```

```


```

```
Linux

```

```
=end

```

#3 - 03/29/2010 09:19 AM - matz (Yukihiko Matsumoto)

```
=begin

```

In message "Re: [ruby-dev:40779] [Feature #3018] UNINITIALIZED_VAR() " on Fri, 26 Mar 2010 22:40:53 +0900, Motohiro KOSAKI redmine@ruby-lang.org writes:

```
gcc
thread.c do_select()

```

```
Linux

```

```


```

```
=end

```

#4 - 03/29/2010 07:45 PM - kosaki (Motohiro KOSAKI)

```
=begin

```

```
Linux

```

```


```

```
IRC

```

```
=end

```

#5 - 03/30/2010 07:01 AM - matz (Yukihiko Matsumoto)

```
=begin

```

In message "Re: [ruby-dev:40831] Re: [Feature #3018] UNINITIALIZED_VAR() " on Mon, 29 Mar 2010 19:45:01 +0900, KOSAKI Motohiro kosaki.motohiro@gmail.com writes:

```
IRC

```

```
cvs-admin@ruby-lang.org gpg ssh2
cvs-

```

```
=end

```

#6 - 03/30/2010 10:24 AM - nahi (Hiroshi Nakamura)

```
=begin

```

0000000000

2010/3/30 Yukihiro Matsumoto matz@ruby-lang.org:

cvs-admin@ruby-lang.org 0 gpg 000000 ssh2 000000
000000cvs-0000000000000000000000

gpg0000→(PGP|OpenPGP)(0000|00)0000000000000000
gpg00OpenPGP0000PGP0000000000000000000000
000000000000(?)0gpg0000000000000000000000
gpg0000000000000000000000

0000Ruby000000000000000000

000Wiki0000000000000000000000

=end

#7 - 03/30/2010 10:52 AM - matz (Yukihiro Matsumoto)

=begin
0000 000000

In message "Re: [ruby-dev:40839] Re: [Feature #3018] UNINITIALIZED_VAR() 000000"
on Tue, 30 Mar 2010 10:23:59 +0900, "NAKAMURA, Hiroshi" nakahiro@gmail.com writes:

|2010/3/30 Yukihiro Matsumoto matz@ruby-lang.org:

|> cvs-admin@ruby-lang.org 0 gpg 000000 ssh2 000000
|> 000000cvs-0000000000000000000000

|
|gpg0000→(PGP|OpenPGP)(0000|00)0000000000000000
|gpg00OpenPGP0000PGP0000000000000000000000
|000000000000(?)0gpg0000000000000000000000
|gpg0000000000000000000000

000000000000000000000000 gpg 000000
0000000000000000000000000000000000
00000000000000000000000000000000
gpg 00000000000000000000000000000000
000000000000000000000000 pgp 0000 gpg
000000000000

00000000(PGP | OpenPGP)0000000000000000
00000000000000000000000000000000

=end

#8 - 03/30/2010 11:13 AM - nahi (Hiroshi Nakamura)

=begin
2010/3/30 Yukihiro Matsumoto matz@ruby-lang.org:

|gpg0000→(PGP|OpenPGP)(0000|00)0000000000000000

000000000000000000000000 gpg 000000
00000000000000000000000000000000
00000000000000000000000000000000
gpg 00000000000000000000000000000000
000000000000000000000000 pgp 0000 gpg
000000000000

0000000000000000000000000000000000

--rfc24400000000000000000000000000000

0000gpg0000→0gpg0000000000000000

=end

#9 - 03/30/2010 11:22 AM - matz (Yukihiro Matsumoto)

=begin
0000 000000

