

Ruby trunk - Bug #3571

[BUG] if rb_notimplement() is called in an anonymous block called by rb_block_call()

07/14/2010 05:52 PM - usa (Usaku NAKAMURA)

Status:	Closed	
Priority:	Normal	
Assignee:	nobu (Nobuyoshi Nakada)	
Target version:	2.0.0	
ruby -v:	ruby 1.9.3dev (2010-07-13 trunk 28631) [i386-mswin32]	Backport:

Description

```
=begin
mswin

require "openssl"
c = OpenSSL::Config.new("NUL")
c["foo"] = "bar", "baz"

ext/openssl/ossl_config.c

(1) ossl_config_set_section()
(2) rb_block_call()
(3) set_conf_section_i() → ossl_config_add_value() → rb_notimplement()
(4) rb_frame_this_func() → frame_func_id()
(5) cfp->me NULL

cfp->me
1.9.2 backport
=end
```

History

#1 - 07/14/2010 08:27 PM - nobu (Nobuyoshi Nakada)

- Status changed from Assigned to Closed

- % Done changed from 0 to 100

```
=begin
This issue was solved with changeset r28642.
Usaku, thank you for reporting this issue.
Your contribution to Ruby is greatly appreciated.
May Ruby be with you.
=end
```