

Ruby master - Bug #3832

Etc.sysconfig contains "\$(DESTDIR)" when ./configure is called with --sysconfdir=

09/15/2010 10:03 PM - eolamey (Eric-Olivier Lamey)

| | | |
|--|--------------|------------------|
| Status: | Closed | Backport: |
| Priority: | Normal | |
| Assignee: | | |
| Target version: | 1.9.2 | |
| ruby -v: | ruby 1.9.2p0 | |
| Description | | |
| <pre>=begin When the Ruby source files are configured for compilation with ./configure and the --sysconfdir= parameter is specified, the "ext/etc/extconf.h" file is generated with a SYSCONFDIR variable that contains "\$(DESTDIR)" literally, not expanded. For example: \$./configure --prefix=/usr --sysconfdir=/etc ... \$ make ... \$ grep SYSCONFDIR ext/etc/extconf.h #define SYSCONFDIR "\$(DESTDIR)/etc" This variable was introduced in r27667 and seems only used in "lib/rubygems/config_file.rb". Why not use Config::CONFIG['sysconfdir'] there (rbconfig is already required by rubygems)? Note: this was verified on Linux RHEL 5 with ruby-1.9.2-p0.tar.bz2. =end</pre> | | |

History

#1 - 09/16/2010 08:28 AM - nobu (Nobuyoshi Nakada)

```
=begin
Hi,
```

(10/09/15 22:03), Eric-Olivier Lamey wrote at [ruby-core:32394]:

```
    This variable was introduced in r27667 and seems only used in
    "lib/rubygems/config_file.rb". Why not use
    Config::CONFIG['sysconfdir'] there (rbconfig is already required by
    rubygems)?
```

It's determined at runtime on Windows.

```
--
Nobu Nakada
```

```
=end
```

#2 - 09/16/2010 08:37 AM - nobu (Nobuyoshi Nakada)

- Status changed from Open to Closed

- % Done changed from 0 to 100

```
=begin
This issue was solved with changeset r29268.
Eric-Olivier, thank you for reporting this issue.
Your contribution to Ruby is greatly appreciated.
May Ruby be with you.
```

```
=end
```