

## Backport187 - Backport #4497

### REXML Pretty formater does use specified 'width' to wrap lines

03/13/2011 04:47 AM - mfrasca (Michael Frasca)

<b>Status:</b>	Closed
<b>Priority:</b>	Normal
<b>Assignee:</b>	
<b>Description</b>	
<pre>=begin REXML::Formatters::Pretty has 'width' attribute used to wrap lines. This is not used when the wrap method is invoked  # pretty.rb - line 86 def write_text( node, output ) s = node.to_s() s.gsub!(/s/, ' ') s.squeeze!(" ") s = wrap(s, 80-@level) ## HERE - 80 is hard coded, value should depend on @width and @level (e.g. @width - @level) s = indent_text(s, @level, " ", true) output &lt;&lt; (' '*@level + s) end =end</pre>	

#### History

##### #1 - 03/14/2011 03:03 AM - mfrasca (Michael Frasca)

- File *ruby-core-bug-4497.patch* added

```
=begin
Patch attached for 'lib/rexml/formatters/pretty.rb'. @width attribute is used to compute line width when wrapping text output. @level is subtracted from @width to account for indenting of current xml node.
```

-Michael Frasca

```
=end
```

##### #2 - 07/15/2019 04:52 PM - jeremyevans0 (Jeremy Evans)

- ruby -v deleted (ruby 1.8.7 (2011-02-18 patchlevel 334) [i386-mingw32])

- Target version deleted (Ruby 1.8.7)

- Status changed from Open to Closed

- Description updated

- Project changed from Ruby 1.8 to Backport187

- Tracker changed from Bug to Backport

#### Files

ruby-core-bug-4497.patch	465 Bytes	03/14/2011	mfrasca (Michael Frasca)
--------------------------	-----------	------------	--------------------------