

Ruby master - Feature #4528

[PATCH] ext/io/nonblock: avoid unnecessary fcntl F_SETFL calls

03/26/2011 03:38 AM - normalperson (Eric Wong)

Status:	Closed	
Priority:	Normal	
Assignee:	kosaki (Motohiro KOSAKI)	
Target version:	1.9.3	
Description		
=begin Avoid F_SETFL if we're not changing the O_NONBLOCK bit. F_SETFL is an expensive operation since it needs to affect all processes with the same file object. rb_io_set_nonblock() implements similar logic to avoid F_SETFL in io.c =end		

History

#1 - 03/26/2011 11:59 AM - kosaki (Motohiro KOSAKI)

- Status changed from Open to Assigned
- Assignee set to kosaki (Motohiro KOSAKI)

=begin
Looks good to me. I'll commit this if nobody put objections.
=end

#2 - 04/17/2011 12:53 AM - kosaki (Motohiro KOSAKI)

- Status changed from Assigned to Closed
- Target version changed from 2.0.0 to 1.9.3

=begin
r31238.
=end

Files

0001-ext-io-nonblock-avoid-unnecessary-fcntl-F_SETFL-call.patch	1.07 KB	03/26/2011	normalperson (Eric Wong)
---	---------	------------	--------------------------