

## Ruby master - Bug #4543

Ripper "`<<-eos\neos`"

03/31/2011 10:01 PM - exkazuu (Kazunori SAKAMOTO)

|   |                  |
|---|------------------|
| <b>Status:</b> Closed   |                  |
| <b>Priority:</b> Normal   |                  |
| <b>Assignee:</b> nobu (Nobuyoshi Nakada)                                |                  |
| <b>Target version:</b> 1.9.3  |                  |
| <b>ruby -v:</b> ruby 1.9.2p180 (2011-02-18 revision 30909) [i686-linux] | <b>Backport:</b> |

### Description

```
=begin
Ripper::SexpBuilder.new(%Q!<<-eos\neos!).parse
on_heredoc_end
```

■

```
ruby 1.9.3dev (2011-03-31 trunk 31223) [i686-linux]
ruby 1.9.2p180 (2011-02-18 revision 30909) [i686-linux]
ruby 1.9.1p431 (2011-02-18 revision 30908) [i686-linux]
```

■

```
require 'ripper'
```

```
class Parser < Ripper::SexpBuilder
  ms = Ripper::SexpBuilder.new("").methods
  defs = ms.map { |s| s.to_s }
  .select { |s| s.start_with?('on_') }
  .map { |s| %Q{
def #{s}(*args)
  print '#{s}:'
  p args
end
}}.join
eval(defs)
end
```

```
def parse(src)
  puts "" + src.inspect + ""
  Parser.new(src).parse
  puts
end
```

```
parse(%Q!<<-eos\neos!)
parse(%Q!<<-eos\n\neos!)
```

■

```
""<<-eos\neos""
on_heredoc_beg: ["<<-eos"]
on_string_content: []
on_string_literal: []
on_nl: ["\n"]
on_stmts_new: []
on_stmts_add: 1, []
on_program: 1, []
```

■

```
""<<-eos\n\neos""
on_heredoc_beg: ["<<-eos"]
on_string_content: []
on_tstring_content: ["\n"]
on_heredoc_end: ["eos"]
on_string_add: 1, ["\n"]
on_string_literal: 1, ["\n"]
```

```
on_nl: ["\n"]
on_stmts_new: []
on_stmts_add: [., [{"", "\n"}]]
on_program: [., [{"", "\n"}]]
=end
```

## History

### #1 - 03/31/2011 10:23 PM - exkazuu (Kazunori SAKAMOTO)

```
=begin
----"<<-eos\neos"----
on_heredoc_beg: ["<<-eos"]
on_string_content: []
on_string_literal: [[]]
on_nl: ["\n"]
on_stmts_new: []
on_stmts_add: [., []]
on_program: [., [[]]]
```

```
----"<<-eos\n\neos"----
on_heredoc_beg: ["<<-eos"]
on_string_content: []
on_tstring_content: ["\n"]
on_heredoc_end: ["eos"]
on_string_add: [., ["\n"]
on_string_literal: [., [{"", "\n"}]]
on_nl: ["\n"]
on_stmts_new: []
on_stmts_add: [., [{"", "\n"}]]
on_program: [., [{"", "\n"}]]
```

=end

### #2 - 03/31/2011 10:24 PM - exkazuu (Kazunori SAKAMOTO)

```
=begin
require 'ripper'

class Parser < Ripper::SexpBuilder
  ms = Ripper::SexpBuilder.new("").methods
  defs = ms.map { |s| s.to_s }
  .select { |s| s.start_with?('on_') }
  .map { |s| %Q{
  def #{s}(*args)
  print '#{s}: '
  p args
  end
  }}.join
  eval(defs)
end
```

```
def parse(src)
  puts "" + src.inspect + ""
  Parser.new(src).parse
  puts
end
```

```
parse(%Q!<<-eos\neos!)
parse(%Q!<<-eos\n\neos!)
```

```
□□□□□□□□□□□□□□□□□□□□□□
=end
```

### #3 - 06/11/2011 05:14 PM - ko1 (Koichi Sasada)

- Category set to ext
- Status changed from Open to Assigned
- Assignee set to nobu (Nobuyoshi Nakada)

### #4 - 06/26/2011 07:01 PM - nahi (Hiroshi Nakamura)

- Target version set to 1.9.3

**#5 - 07/06/2011 03:07 PM - nobu (Nobuyoshi Nakada)**

- *Status changed from Assigned to Closed*

- *% Done changed from 0 to 100*

r32412□□□□□□□□