

## Ruby master - Feature #4936

### Android WEBrick Digest

06/27/2011 08:24 PM - blueday (blue day)

<b>Status:</b>	Closed
<b>Priority:</b>	Normal
<b>Assignee:</b>	naruse (Yui NARUSE)
<b>Target version:</b>	1.9.3
<b>Description</b> Android Digest Authorization algorithm=MD5 algorithm=md5 WEBrick  WEBrick OperaHack	

#### Associated revisions

##### Revision 8fb2058d - 07/05/2011 05:06 AM - naruse (Yui NARUSE)

- lib/webrick/httpauth/digestauth.rb (\_authenticate):  
Literal texts in HTTP ABNF is case-insensitive (RFC2616 2.1), and a ample implementation in RFC2617 also ignores the case of algorithms. So now this ignores those cases.  
[ruby-dev:43965] [Feature #4936]
- lib/webrick/httpauth/digestauth.rb (initialize):  
Because of above, opera\_hack is useless and removed.

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@32410 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

##### Revision 32410 - 07/05/2011 05:06 AM - naruse (Yui NARUSE)

- lib/webrick/httpauth/digestauth.rb (\_authenticate):  
Literal texts in HTTP ABNF is case-insensitive (RFC2616 2.1), and a ample implementation in RFC2617 also ignores the case of algorithms. So now this ignores those cases.  
[ruby-dev:43965] [Feature #4936]
- lib/webrick/httpauth/digestauth.rb (initialize):  
Because of above, opera\_hack is useless and removed.

##### Revision 32410 - 07/05/2011 05:06 AM - naruse (Yui NARUSE)

- lib/webrick/httpauth/digestauth.rb (\_authenticate):  
Literal texts in HTTP ABNF is case-insensitive (RFC2616 2.1), and a ample implementation in RFC2617 also ignores the case of algorithms. So now this ignores those cases.  
[ruby-dev:43965] [Feature #4936]
- lib/webrick/httpauth/digestauth.rb (initialize):  
Because of above, opera\_hack is useless and removed.

##### Revision 32410 - 07/05/2011 05:06 AM - naruse (Yui NARUSE)

- lib/webrick/htppauth/digestauth.rb (\_authenticate):  
Literal texts in HTTP ABNF is case-insensitive (RFC2616 2.1), and a ample implementation in RFC2617 also ignores the case of algorithms. So now this ignores those cases.  
[ruby-dev:43965] [Feature #4936]
- lib/webrick/htppauth/digestauth.rb (initialize):  
Because of above, opera\_hack is useless and removed.

**Revision 32410 - 07/05/2011 05:06 AM - naruse (Yui NARUSE)**

- lib/webrick/htppauth/digestauth.rb (\_authenticate):  
Literal texts in HTTP ABNF is case-insensitive (RFC2616 2.1), and a ample implementation in RFC2617 also ignores the case of algorithms. So now this ignores those cases.  
[ruby-dev:43965] [Feature #4936]
- lib/webrick/htppauth/digestauth.rb (initialize):  
Because of above, opera\_hack is useless and removed.

**Revision 32410 - 07/05/2011 05:06 AM - naruse (Yui NARUSE)**

- lib/webrick/htppauth/digestauth.rb (\_authenticate):  
Literal texts in HTTP ABNF is case-insensitive (RFC2616 2.1), and a ample implementation in RFC2617 also ignores the case of algorithms. So now this ignores those cases.  
[ruby-dev:43965] [Feature #4936]
- lib/webrick/htppauth/digestauth.rb (initialize):  
Because of above, opera\_hack is useless and removed.

**Revision 32410 - 07/05/2011 05:06 AM - naruse (Yui NARUSE)**

- lib/webrick/htppauth/digestauth.rb (\_authenticate):  
Literal texts in HTTP ABNF is case-insensitive (RFC2616 2.1), and a ample implementation in RFC2617 also ignores the case of algorithms. So now this ignores those cases.  
[ruby-dev:43965] [Feature #4936]
- lib/webrick/htppauth/digestauth.rb (initialize):  
Because of above, opera\_hack is useless and removed.

**History**

---

**#1 - 06/29/2011 01:46 AM - naruse (Yui NARUSE)**

- Status changed from Open to Assigned
- Assignee set to naruse (Yui NARUSE)
- Target version changed from 2.0.0 to 1.9.3

Opera hack Android

**#2 - 07/05/2011 02:06 PM - naruse (Yui NARUSE)**

- Status changed from Assigned to Closed
- % Done changed from 0 to 100

This issue was solved with changeset r32410.  
blue, thank you for reporting this issue.  
Your contribution to Ruby is greatly appreciated.  
May Ruby be with you.

---

- lib/webrick/httpauth/digestauth.rb (\_authenticate):  
Literal texts in HTTP ABNF is case-insensitive (RFC2616 2.1),  
and a ample implementation in RFC2617 also ignores the case  
of algorithms. So now this ignores those cases.  
[ruby-dev:43965] [Feature [#4936](#)]
- lib/webrick/httpauth/digestauth.rb (initialize):  
Because of above, opera\_hack is useless and removed.