

Backport200 - Backport #8054

open-uri resolv-replace

03/09/2013 03:37 PM - mrkn (Kenta Murata)

Status:	Closed				
Priority:	Normal				
Assignee:	nagachika (Tomoyuki Chikanaga)				
Description	<pre>open-uri resolv-replace \$ ruby -ropen-uri -rresolv-replace -ve 'open("http://www.ruby-lang.org/")' ruby 2.0.0p0 (2013-02-24 revision 39474) [x86_64-darwin12.2.0] /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/resolv.rb:1176:in create': cannot interpret as DNS name: nil (ArgumentError) from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/resolv.rb:1022:in generate_candidates' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/resolv.rb:1047:in resolv' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/resolv.rb:513:in each_resource' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/resolv.rb:406:in each_address' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/resolv.rb:115:in block in each_address' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/resolv.rb:114:in each' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/resolv.rb:114:in each_address' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/resolv.rb:92:in getaddress' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/resolv.rb:43:in getaddress' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/resolv-replace.rb:10:in getaddress' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/resolv-replace.rb:22:in initialize' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/net/http.rb:877:in open' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/net/http.rb:877:in block in connect' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/timeout.rb:51:in timeout' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/net/http.rb:876:in connect' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/net/http.rb:861:in do_start' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/net/http.rb:850:in start' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/open-uri.rb:313:in open_http' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/open-uri.rb:708:in buffer_open' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/open-uri.rb:210:in block in open_loop' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/open-uri.rb:208:in catch' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/open-uri.rb:208:in open_loop' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/open-uri.rb:149:in open_uri' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/open-uri.rb:688:in open' from /Users/kenta-murata/.rbenv/versions/2.0.0-p0/lib/ruby/2.0.0/open-uri.rb:34:in open' from -e:1:in `'</pre>				
Related issues:	<table border="1"><tr><td>Related to Ruby master - Bug #8113: ArgumentError: cannot interpret as DNS na...</td><td>Closed</td><td>03/18/2013</td></tr></table>		Related to Ruby master - Bug #8113: ArgumentError: cannot interpret as DNS na...	Closed	03/18/2013
Related to Ruby master - Bug #8113: ArgumentError: cannot interpret as DNS na...	Closed	03/18/2013			

Associated revisions

Revision b1f2effd - 03/11/2013 01:47 PM - akr (Akira Tanaka)

- lib/resolv-replace.rb (TCPSocket#initialize): resolve the 3rd argument only if non-nil value is given. [ruby-dev:47150] [ruby-trunk - Bug #8054] reported and analyzed by mrkn.

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@39725 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision 39725 - 03/11/2013 01:47 PM - akr (Akira Tanaka)

- lib/resolv-replace.rb (TCPSocket#initialize): resolve the 3rd argument only if non-nil value is given. [ruby-dev:47150] [ruby-trunk - Bug #8054] reported and analyzed by mrkn.

Revision 39725 - 03/11/2013 01:47 PM - akr (Akira Tanaka)

- lib/resolv-replace.rb (TCPSocket#initialize): resolve the 3rd argument only if non-nil value is given. [ruby-dev:47150] [ruby-trunk - Bug #8054] reported and analyzed by mrkn.

Revision 39725 - 03/11/2013 01:47 PM - akr (Akira Tanaka)

- lib/resolv-replace.rb (TCPSocket#initialize): resolve the 3rd argument only if non-nil value is given. [ruby-dev:47150] [ruby-trunk - Bug #8054] reported and analyzed by mrkn.

Revision 39725 - 03/11/2013 01:47 PM - akr (Akira Tanaka)

- lib/resolv-replace.rb (TCPSocket#initialize): resolve the 3rd argument only if non-nil value is given. [ruby-dev:47150] [ruby-trunk - Bug #8054] reported and analyzed by mrkn.

Revision 39725 - 03/11/2013 01:47 PM - akr (Akira Tanaka)

- lib/resolv-replace.rb (TCPSocket#initialize): resolve the 3rd argument only if non-nil value is given. [ruby-dev:47150] [ruby-trunk - Bug #8054] reported and analyzed by mrkn.

Revision 39725 - 03/11/2013 01:47 PM - akr (Akira Tanaka)

- lib/resolv-replace.rb (TCPSocket#initialize): resolve the 3rd argument only if non-nil value is given. [ruby-dev:47150] [ruby-trunk - Bug #8054] reported and analyzed by mrkn.

Revision d825fc8d - 04/03/2013 05:27 PM - nagachika (Tomoyuki Chikanaga)

merge revision(s) 39725: [Backport #8054]

```
* lib/resolv-replace.rb (TCPSocket#initialize): resolve the 3rd
argument only if non-nil value is given.
[ruby-dev:47150] [ruby-trunk - Bug #8054] reported and analyzed by
mrkn.
```

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/branches/ruby_2_0_0@40089 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision 40089 - 04/03/2013 05:27 PM - nagachika (Tomoyuki Chikanaga)

merge revision(s) 39725: [Backport #8054]

```
* lib/resolv-replace.rb (TCPSocket#initialize): resolve the 3rd
argument only if non-nil value is given.
[ruby-dev:47150] [ruby-trunk - Bug #8054] reported and analyzed by
mrkn.
```

History

#1 - 03/11/2013 10:04 AM - mrkn (Kenta Murata)

XXXXXXXXXXXXXXXXXXXXXXXXXX:

```
diff --git a/lib/resolv-replace.rb b/lib/resolv-replace.rb
index ff34f90..374c81a 100644
--- a/lib/resolv-replace.rb
+++ b/lib/resolv-replace.rb
@@ -18,9 +18,9 @@ class TCPSocket < IPSocket
# :stopdoc:
alias original_resolv_initialize initialize
# :startdoc:
```

- def initialize(host, serv, *rest)
- rest[0] = IPSocket.getaddress(rest[0]) unless rest.empty?
- original_resolv_initialize(IPSocket.getaddress(host), serv, *rest)
- def initialize(host, serv, local_host=nil, local_serv=nil)
- local_host = IPSocket.getaddress(local_host) if local_host
- original_resolv_initialize(IPSocket.getaddress(host), serv, local_host, local_serv) end end

#2 - 03/11/2013 02:07 PM - mrkn (Kenta Murata)

```
XXXXXXXXXXXXXXXXXXXXXXXXXX r36367 XXXXXXXXXXXXXXXXXXXX
r36367 Net::HTTP#connect TCPSocket.open 3XXXXXXXXX4XXXX
XXXXXXXXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXX resolv-replace.rb XXXXXXXXXXXXXXXXXXXX
resolv-replace XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
```

#3 - 03/11/2013 10:47 PM - akr (Akira Tanaka)

- Status changed from Open to Closed

- % Done changed from 0 to 100

This issue was solved with changeset r39725.
Kenta, thank you for reporting this issue.
Your contribution to Ruby is greatly appreciated.
May Ruby be with you.

- lib/resolv-replace.rb (TCPSocket#initialize): resolve the 3rd argument only if non-nil value is given. [ruby-dev:47150] [ruby-trunk - Bug #8054] reported and analyzed by mrkn.

#4 - 03/11/2013 10:53 PM - akr (Akira Tanaka)

2013/3/11 mrkn (Kenta Murata) muraken@gmail.com:

Issue #8054 has been updated by mrkn (Kenta Murata).

~~~~~

```
diff --git a/lib/resolv-replace.rb b/lib/resolv-replace.rb
index ff34f90..374c81a 100644
--- a/lib/resolv-replace.rb
+++ b/lib/resolv-replace.rb
@@ -18,9 +18,9 @@ class TCPSocket < IPSTicket
# :stopdoc:
alias original_resolv_initialize initialize
# :startdoc:
```

- def initialize(host, serv, \*rest)
- rest[0] = IPSTicket.getaddress(rest[0]) unless rest.empty?
- original\_resolv\_initialize(IPSTicket.getaddress(host), serv, \*rest)
- def initialize(host, serv, local\_host=nil, local\_serv=nil)
- local\_host = IPSTicket.getaddress(local\_host) if local\_host
- original\_resolv\_initialize(IPSTicket.getaddress(host), serv, local\_host, local\_serv) end end

~~~~~  
r39725 ~~~~~
--
[Tanaka Akira]

#5 - 03/12/2013 12:08 AM - nagachika (Tomoyuki Chikanaga)

- Tracker changed from Bug to Backport
- Project changed from Ruby master to Backport200
- Category deleted (lib)
- Status changed from Closed to Assigned
- Assignee changed from akr (Akira Tanaka) to nagachika (Tomoyuki Chikanaga)

#6 - 04/04/2013 02:27 AM - nagachika (Tomoyuki Chikanaga)

- Status changed from Assigned to Closed

This issue was solved with changeset r40089.
Kenta, thank you for reporting this issue.
Your contribution to Ruby is greatly appreciated.
May Ruby be with you.

merge revision(s) 39725: [Backport #8054]

```
* lib/resolv-replace.rb (TCPSocket#initialize): resolve the 3rd
argument only if non-nil value is given.
[ruby-dev:47150] [ruby-trunk - Bug #8054] reported and analyzed by
mrkn.
```