

## Ruby master - Feature #8675

### Add Readline.point=(pos)

07/24/2013 03:03 AM - naruse (Yui NARUSE)

<b>Status:</b>	Closed
<b>Priority:</b>	Normal
<b>Assignee:</b>	kouji (Kouji Takao)
<b>Target version:</b>	2.1.0
<b>Description</b>	
r42146 00000000 \A 00000000000000rl_point 00000000000000000000	
diff --git a/ext/readline/readline.c b/ext/readline/readline.c index 714b08c..03ab724 100644 --- a/ext/readline/readline.c +++ b/ext/readline/readline.c @@ -808,6 +808,12 @@ readline_s_get_point(VALUE self) { return INT2NUM(rl_point); } +static VALUE +readline_s_set_point(VALUE self, VALUE pos) +{ <ul style="list-style-type: none"><li>• rl_point = NUM2INT(pos);</li><li>• return pos; +} #else #define readline_s_get_point rb_f_notimplement #endif @@ -1761,6 +1767,8 @@ Init_readline() readline_s_get_line_buffer, 0); rb_define_singleton_method(mReadline, "point", readline_s_get_point, 0);</li><li>• rb_define_singleton_method(mReadline, "point=",</li><li>• readline_s_set_point, 1); rb_define_singleton_method(mReadline, "set_screen_size", readline_s_set_screen_size, 2); rb_define_singleton_method(mReadline, "get_screen_size",</li></ul>	

#### Associated revisions

##### Revision a78713ce - 08/06/2013 12:52 PM - kouji (Kouji Takao)

- ext/readline/readline.c (readline\_s\_set\_point, Init\_readline): add Readline.point=(pos). Patched by naruse. [ruby-dev:47535] [Feature #8675]

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@42405 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

##### Revision 42405 - 08/06/2013 12:52 PM - kouji (Kouji Takao)

- ext/readline/readline.c (readline\_s\_set\_point, Init\_readline): add Readline.point=(pos). Patched by naruse. [ruby-dev:47535] [Feature #8675]

##### Revision 42405 - 08/06/2013 12:52 PM - kouji (Kouji Takao)

- ext/readline/readline.c (readline\_s\_set\_point, Init\_readline): add Readline.point=(pos). Patched by naruse. [ruby-dev:47535] [Feature #8675]

##### Revision 42405 - 08/06/2013 12:52 PM - kouji (Kouji Takao)

- ext/readline/readline.c (readline\_s\_set\_point, Init\_readline): add Readline.point=(pos). Patched by naruse. [ruby-dev:47535] [Feature #8675]

##### Revision 42405 - 08/06/2013 12:52 PM - kouji (Kouji Takao)

- ext/readline/readline.c (readline\_s\_set\_point, Init\_readline): add Readline.point=(pos). Patched by naruse. [ruby-dev:47535] [Feature #8675]

##### Revision 42405 - 08/06/2013 12:52 PM - kouji (Kouji Takao)

- ext/readline/readline.c (readline\_s\_set\_point, Init\_readline): add Readline.point=(pos). Patched by naruse. [ruby-dev:47535] [Feature #8675]

##### Revision 42405 - 08/06/2013 12:52 PM - kouji (Kouji Takao)

- ext/readline/readline.c (readline\_s\_set\_point, Init\_readline): add Readline.point=(pos). Patched by naruse. [ruby-dev:47535] [Feature #8675]

**History**

---

**#1 - 07/26/2013 11:39 AM - kouji (Kouji Takao)**

- Due date set to 07/31/2013

```

00000000000000000000
70000000000000000000
00000000000000000000ribedit00000000
  
```

**#2 - 08/06/2013 09:04 PM - kouji (Kouji Takao)**

```

00000000000000000000 42146 00000000
Readline.delete_text GNU
Readline0000000000Readline.point00000000000000000000000000test_readline.rb0000Readline.point0000000000000000000000000000000000
00000000000000000000

00000000000000Readline.point=00000000

0000Readline.delete_text00Readline.point0000000000000000000000000000000000000000000000000000000000000000000000
  
```

**#3 - 08/06/2013 09:47 PM - kouji (Kouji Takao)**

- Tracker changed from Bug to Feature

**#4 - 08/06/2013 09:52 PM - kouji (Kouji Takao)**

- Status changed from Assigned to Closed
- % Done changed from 0 to 100

This issue was solved with changeset r42405.  
 Yui, thank you for reporting this issue.  
 Your contribution to Ruby is greatly appreciated.  
 May Ruby be with you.

---

- ext/readline/readline.c (readline\_s\_set\_point, Init\_readline): add Readline.point=(pos). Patched by naruse. [ruby-dev:47535] [Feature [#8675](#)]